

65" DURASCREEN KX DIGITAL <u>SIGNAGE</u>

Full Sun Outdoor Display

PVO65DSA



The **ProofVision Durascreen KX 65**" is a commercial-grade outdoor digital signage solution built for reliable performance in challenging environments. With a 2500-nit high-brightness panel, IP66-rated enclosure, IK10 impact resistance, and an integrated Android OS, it's ready for seamless integration into AV systems across retail, transport, and public spaces. Its slimline form factor and all-weather durability make it a practical choice for exposed or space-constrained installations, delivering consistent visibility and minimal maintenance over time.

Perfect for

Outdoor retail & large-format signage

Public venue communications

Smart cities and transport hubs

Hospitality, entertainment & sports venues

Wayfinding & digital advertising networks

Key Features



4K UHD Resolution

Ultra-sharp picture quality at scale



Ultra-Bright 2500-nits Display

Readable even in full sunlight



IP66 Weatherproof Enclosure

Dustproof, waterproof, and built to withstand all weather



IK10 Anti-Vandal Protection

Tempered glass resists heavy impact



Integrated Android OS

No external media player needed



Automatic Brightness Adjustment

Ambient light sensor for optimal visibility and energy savings

24/7

24/7 Operation

Designed for continuous commercial use



Landscape & Portrait Mounting

Flexible orientation for any application



For more information Call + 44 (0) 203 4111 693 or email sales@proofvision.co.uk

ProofVision, Unit 1, Avad House, Belvue Road, Northolt, London UB5 5HY

Specification

| LED Spec | |
|------------------------|---------------------------|
| Panel size | 65 inches |
| Resolution | 3840 x 2160 (4K UHD) |
| Brightness | 2500 cd/m ² |
| Contrast ratio | 1200:1 |
| Viewing angle | 178° / 178° |
| Backlight Type | Direct LED |
| Operation Life | 50,000 hours |
| Colour Depth | 8-bit |
| Colour Gamut | 72% |
| Response time | 8ms |
| Refresh rate | 60Hz |
| Environmental | |
| Operating temperature | -30°C to 50°C |
| Impact Rating | IK10 |
| Humidity | 5% to 98% |
| Waterproof rating | IP66 |
| Inputs/Outputs | |
| HDMI | x 1 |
| USB | x 1 |
| RJ45 Ethernet | x 1 |
| Audio out | x 1 (3.5mm Jack) |
| Wi-Fi | Yes |
| Power | |
| Input Voltage | 110~220V AC ±10%, 50/60Hz |
| Power Consumption | 460W |
| Physical | |
| Dimensions (W x H x D) | 900 x 1524 x 107mm |
| Net Weight | 63kg |
| Mounting | VESA 600 x 620 mm |
| Material | Aluminium |
| Finish | Fine-grain powder coating |
| Colour | Black |
| Glass | AG-coated tempered glass |
| Orientation | Landscape or Portrait |

Included

Remote control

User manual

3-year commercial warranty

E&OE PVO65DSA