



75" DURASCREEN KX DIGITAL SIGNAGE

Full Sun Outdoor Display

PVO75DSA



The **ProofVision 75" Durascreen KX** is a high-performance outdoor digital signage display designed to make a big impact in any setting. With a 2500-nit ultra-bright panel, fully weatherproof IP66-rated enclosure, IK10 impact resistance, and an integrated Android OS, it delivers clear, vibrant content around the clock. Whether used for advertising, public information, or wayfinding, this large-format screen combines durability, visibility, and reliability for a wide range of outdoor environments.

Perfect for

High-traffic commercial environments

Outdoor digital advertising networks

Transportation terminals

Stadiums and entertainment venues

Smart city infrastructure

Key Features



4K UHD Resolution

Pin-sharp visuals across a massive screen area



Ultra-Bright 2500-nits Display

Readable even in full sunlight



IP66 Weatherproof Enclosure

Fully sealed against water, dust, and debris



IK10 Impact Resistance

AG-coated tempered glass built to withstand vandalism



Integrated Android OS

No external media player needed



Automatic Brightness Adjustment

Adapts to changing light conditions for visibility and efficiency



24/7 Operation

Built to run around the clock



Landscape & Portrait Mounting

Flexible orientation for any application

Specification

LED Spec

| | |
|----------------|------------------------|
| Panel size | 75 inches |
| Resolution | 3840 x 2160 (4K UHD) |
| Brightness | 2500 cd/m ² |
| Contrast ratio | 1200:1 |
| Viewing angle | 178° / 178° |
| Backlight Type | Direct LED |
| Operation Life | 50,000 hours |
| Colour Depth | 8-bit |
| Colour Gamut | 72% |
| Response time | 8ms |
| Refresh rate | 60Hz |

Environmental

| | |
|-----------------------|---------------|
| Operating temperature | -30°C to 50°C |
| Impact Rating | IK10 |
| Humidity | 5% to 98% |
| Waterproof rating | IP66 |

Inputs/Outputs

| | |
|---------------|------------------|
| HDMI | x 1 |
| USB | x 1 |
| RJ45 Ethernet | x 1 |
| Audio out | x 1 (3.5mm Jack) |
| Wi-Fi | Yes |

Power

| | |
|-------------------|---------------------------|
| Input Voltage | 110~220V AC ±10%, 50/60Hz |
| Power Consumption | 540W |

Physical

| | |
|------------------------|--|
| Dimensions (W x H x D) | 1024 x 1745.5 x 107 mm |
| Net Weight | 80kg |
| Mounting | VESA 700 x 700 mm |
| Material | Aluminium |
| Finish | Fine-grain powder coating |
| Colour | Black |
| Glass | AG-coated tempered glass, back-painted Pantone Black C |
| Orientation | Landscape or Portrait |

Included

| | |
|----------------------------|-------------|
| Remote control | User manual |
| 3-year commercial warranty | |



For more information

Call + 44 (0) 203 4111 693

or email sales@proofvision.co.uk

ProofVision, Unit 1, Avad House, Belvue Road,
Northolt, London UB5 5HY